

Enable Manager to Work with Windows XP Firewall

Summary

Installing Microsoft Windows XP Service Pack 2 installs and enables the Windows firewall by default. The Windows Firewall, in its default configuration, will block all Manager network activity. The Windows Firewall Configuration must be modified to allow Manager to function properly.

Details

ACS has a utility that will configure the Windows Firewall to allow Manager to function correctly. To use this utility, follow the instructions below.

Allow Manager to work through the Windows Firewall Configuration

1. Download [ICFCONFIG.EXE](#)
2. Run the utility on a workstation with Manager installed using the following command:
ICFCONFIG -e NSM
3. This will create all the required entries in the Windows Firewall Configuration to allow Manager to function correctly.

The ICFCONFIG utility can also be used to remove Manager from the Windows Firewall Configuration. See below for all the ICFCONFIG Command line options

Full Syntax for the ICFCONFIG utility

```
icfconfig [options] PRODUCT
```

options:

- e enable product in Windows Firewall
- d disable product in Windows Firewall
- r remove product from Windows Firewall

PRODUCT:

NSS – SoftLINK

NSM – Manager

DNA – DNA

ALL - Configures for all installed products

Note:

The Deploy application uses Microsoft File and Print Sharing to remotely install Manager. If you need to use Deploy to deploy to a machine that has the Windows Firewall enabled, you must enable File and Print Sharing in the Windows Firewall Configuration.